

MDL-SN-808/6~12W



INFRARED DIODE LASER AT 808nm

Diode infrared laser module at 808nm is made features of ultra compact, long lifetime and easy operating, which is used in measurement, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	808±3	
Operating mode	CW	
Output power (W)	>6, 7 ... , 12	
Power stability (rms, over 4 hours)	<2%, <1%, <0.5%	
Transverse mode	Multimode	
Beam diameter at the aperture (1/e ² , mm)	~5×8	
Beam divergence, full angle (mrad)	<3.0	
Warm-up time (minutes)	<5	
Beam height from base plate (mm)	11	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz optional	
Expected lifetime (hours)	10000	
Warranty period	1 year	



MDL-SN-808	PSU-H-LED	PSU-H-FDA
<p>129 (L) × 63 (W) × 51 (H) mm³, 0.7 kg</p>	<p>203.6 (L) × 145 (W) × 106 (H) mm³, 2.0 kg</p>	<p>203.6 (L) × 145 (W) × 106 (H) mm³, 2.0 kg</p>