



MSL-FN-457/1~350mW



SINGLE LONGITUDINAL MODE BLUE LASER AT 457nm

All solid state single longitudinal mode blue laser at 457nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in DNA sequencing, flow cytometry, cell sorting, optical instrument, spectrum analysis, interference, measurement, holography, brillouin scattering, physics experiment, etc.



SPECIFICATIONS

Wavelength (nm)	457±1	
Operating mode	CW	
Output power (mW)	>1, 5, 10, 20, ..., 150	>150, 160, ..., 350
Power stability (rms, over 4 hours)	<1%, <2%, <3%	<2%, <3%, <5%
Transverse mode	TEM ₀₀	Near TEM ₀₀
Longitudinal mode	Single	
Spectral linewidth (nm)	<0.00001	
Coherent length (m)	>50	
Noise of amplitude (rms, 1Hz~20MHz)	<1%, typical<0.5%	
M ² factor	<1.2	
Beam diameter at the aperture (1/e ² , mm)	<2.0	
Beam divergence, full angle (mrad)	<1.2	
Polarization ratio	>100:1, Vertical±5 degree (Horizontal Optional)	
Warm-up time (minutes)	<10	
Pointing stability after warm-up (mrad)	<0.05	
Beam height from base plate (mm)	27.4	
Operating temperature (°C)	15~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	10000	
Warranty	1 year	

Note: The laser head needs to be used on a heat sink with good heat dissipation.



AVOID EXPOSURE Laser radiation is emitted from this APERTURE

DANGER

LASER RADIATION - AVOID DIRECT EXPOSURE TO BEAM

PEAK POWER<50mW WAVELENGTH 457nm

CLASS IIIb LASER PRODUCT

This device complies with 21 CFR1040.10 and 1040.11

Changchun New Industries Optoelectronics Tech. Co., Ltd. (CN)

888 JinHu Road High-tech Zone Changchun, China

MSL-FN-457	PSU-H-FDA
<p>197(L)×70(W)×50(H) mm³, 1.5 kg</p>	<p>275(L)×145(W)×104(H) mm³, 2.3 kg</p>