



MSL-FN-671/1~500mW




**SINGLE LONGITUDINAL MODE
RED LASER AT 671nm**

All solid state single longitudinal mode red laser at 671nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in DNA sequencing, flow cytometry, cell sorting, optical instrument, spectrum analysis, interference, measurement, holography, brillouin scattering, physics experiment, etc.



SPECIFICATIONS

Wavelength (nm)	671±1	
Operating mode	CW	
Output power (mW)	>1, 5, 10, 20, ... , 300	>300, ... , 500
Power stability (rms, over 4 hours)	<1%, <2%, <3%	<2%, <3%
Transverse mode	TEM ₀₀	
Longitudinal mode	Single	
Spectral linewidth (nm)	<0.00001	
Coherent length (m)	>50	
Noise of amplitude (rms, 1Hz~20MHz)	<1%, typical<0.5%	
M ² factor	<1.2(<1.1 optional)	<1.2
Beam diameter at the aperture (1/e ² , mm)	<2.0, typical<1.5	
Beam divergence, full angle (mrad)	<1.2	
Polarization ratio	>100:1, Vertical±5 degree (Horizontal Optional)	
Warm-up time (minutes)	<10	
Pointing stability after warm-up (mrad)	<0.05	
Beam height from base plate (mm)	27.4	
Operating temperature (°C)	15~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	10000	
Warranty	1 year	



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MSL-FN-671	PSU-H-FDA
<p>197(L)×70(W)×50(H) mm³, 1.5 kg</p>	<p>275(L) ×145(W) ×104(H) mm³, 2.3 kg</p>