

Beam Profiler



Features:

- Spectral range: 340-1100nm
- Beam diameter: 50μm~12.8mm
- Maximum power to 1W
- PC software

SPECIFICATIONS

Product Name	CN0512VIS-B
Spectral Range	340~1100nm
Sensor Size	12.8*12.8mm
Resolution	2560*2560
Dynamic Range	65dB
Pixel Size	5μm
Exposure Time	0.05ms~500ms
Shutter Type	Global Shutter cMOS
Beam Diameter	50μm~12.8mm
Maximum Power Density	50W/cm ² (OD3.0)
Maximum Energy Density	1(J/cm ²)
Maximum Power	1W
Attenuator	general band: OD0.5/OD1/OD2/OD3 (340-1100nm)
Communication Interface	USB3.0
Full Resolution Frame Rate	2-5fps ^①
External Triggering	Available
Dimensions	Reference structure diagram
Operating Environment	Temperature<0~35°C ^② ; Relative humidity<60%; Pointing test temperature: 15-25°C
Operating System	Windows 10/11, 64-bit, pre-installed MS Office or WPS Hardware configuration: ≥8G memory, CPU frequency ≥ 2.5G, core ≥ 4, i5 and above are recommended, and the best display resolution is 1920*1080
Weight (g)	<500
Warranty	1 year

Note: 1. This parameter refers to the frame rate at 5 million pixels.

2. This is the operating temperature, if it involves directivity test, the temperature should be controlled at 15-25°C.

CN0512VIS-B

