




UV-FN-xxx-SLM series

LD PUMPED ALL-SOLID-STATE UV LASER

An all-solid-state single longitudinal mode UV laser is characterized by high output power stability, a good beam profile, ultra - compactness, a long lifetime, and easy operation. The laser is widely used in high - precision measurement, biomedical detection, semiconductor microfabrication, flow cytometry, Raman spectroscopy, photoluminescence, confocal and super - resolution fluorescence microscopy, among other fields.



SPECIFICATIONS

Wavelength (nm)	349±1
Operating mode	CW
Output power (mW) ¹	50-100
Power stability (rms, 4 hours±3°C)	<1%, <0.5%
Spectral line width (MHz)	<1MHz
Transverse mode	TEM ₀₀
M ²	<1.2
Beam diameter at the aperture (1/e ² , mm)	~0.7
Beam divergence, full angle (mrad)	<1.0
Noise of amplitude (rms, 20Hz-20MHz)	<0.25%
Peak-to-Peak Noise (%) (20 Hz to 20 kHz)	<1%
Polarization ratio	>100:1, Vertical (Horizontal optional)
Warm-up time (minutes)	<10
Pointing Stability(μrad) (over 2 hours after warm-up and ±3°C)	<30
Pointing Stability Over Temperature(μrad/°C)	<8
Beam height from base plate (mm)	19
Operating Temperature (°C)	10-35
Operating voltage (VDC)	12V
Expected lifetime (hours)	>10000

LASER HEAD ²	POWER SUPPLY (100-240VAC) optional
<p>Light outlet</p> <p>18 80 70 19</p> <p>140</p> <p>4-φ3.5 Through hole</p> <p>129.5 65</p> <p>125(L)×70(W)×45(H) mm³, 1.0kg</p>	<p>32 145 60</p> <p>145(L)×60(W)×32(H) mm³, 0.5kg</p>

1 Any power level can be selected in this range.

2 The laser head needs to be used on a heat sink with good heat dissipation.